

Inside Mount and Outside Mount Installation Guide

Bracket Installation Kit

Parts list



Inside mount bracket



Outside mount bracket



#8x1 ½ hex head Phillips screw, Nuts & bolts

Installation Guide

***Before proceeding, decide the appropriate mount type depending on your window frame.**

***Do not put a screw directly into drywall.**

For installation requiring *Outside Mount* brackets



1. Depending on the type of brackets you have, you can join the inside mount bracket with the outside mount bracket using the nuts and bolts provided or;



by twisting and locking the inside mount bracket to the outside mount bracket.



2. Place bracket in desired position
 - Mark and pre drill using a drill bit (Optional)
 - Install bracket using provided #8x1 ½ hex head screws.

*Proceed to STEP 3 (Fitting shades into the brackets)

For installation requiring *Inside Mount* brackets



1. Place bracket in the window frame as shown.
 - Mark and pre-drill using a drill bit (Optional).



2. Install bracket using provided #8x1 ½ hex head screws

Fitting shades into the brackets



3. Hook the inner rail along with the front of the bracket.
4. With the front of the bracket and inner rail in place, attach the head rail by firmly pushing up on the rear portion of the head rail.**
Lower the fabric slightly to have easier access. Do this for both sides.



**You will hear a snap ensuring that the head rail has been secured.

****ABBA is not responsible for damage arising from failure to follow instructions. Use electric power tool and provided screws.**

Child Safety Device Installation Guide

Child Safety Kit

Parts list



Tension device



Mounting bracket Wood screw #4, Wood screw #2

Child Safety Device Installation Guide

*Important: tension device must be pulled down and installed to free up the continuous cord and allow control of the shade. If installed improperly, the cord will not move freely. Please refer to diagram.



1. Attach the tension device to the bracket using provided #2 wood screw.



2. Pull down and hold the bracket making sure the cord is free of tension and runs freely



3. Position the bracket on the wall either on the inside or outside of the frame, while holding down on the bracket.



4. Mark the holes and pre-drill while continuing to hold the bracket down. Once marked, remove the bracket from the tension device for installation.



5. Install bracket using provided #4 Wood screws. Reattach the child safety tension device to the bracket using provided #2 wood screws. (Refer to picture for completed installation)



**The continuous cord should move freely without any hesitation.